




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>5</sup> : <b>B01F 7/00, D21C 9/10</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 93/07961</b> (43) International Publication Date: <b>29 April 1993 (29.04.93)</b></p>
<p>(21) International Application Number: <b>PCT/FI92/00276</b> (22) International Filing Date: <b>16 October 1992 (16.10.92)</b> (30) Priority data: <b>914922</b> <b>18 October 1991 (18.10.91)</b> <b>FI</b> (71) Applicant (for all designated States except US): <b>A. AHLSTROM CORPORATION [FI/FI]; SF-29600 Noor-markku (FI).</b> (72) Inventors; and (75) Inventors/Applicants (for US only): <b>MÄKELÄ, Mika [FI/FI]; Hillerinkatu 3 D, SF-49210 Huutjärvi (FI). NIS-KANEN, Toivo [FI/FI]; Maariankatu 10 B 18, SF-49400 Hamina (FI). PELTONEN, Kari [FI/FI]; Isännänraitti 6 A 5, SF-48600 Karhula (FI).</b></p>		<p>(74) Agent: <b>A. AHLSTROM CORPORATION; Patent Department, P.O. Box 18, SF-48601 Karhula (FI).</b>  (81) Designated States: <b>CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE).</b>  Published <i>With international search report.</i> <i>With amended claims and statement.</i></p>

(54) Title: **METHOD AND APPARATUS FOR MIXING A FIRST MEDIUM TO A SECOND MEDIUM AND A BLEACHING PROCESS APPLYING SAID METHOD**

## (57) Abstract

The present invention relates to a mixing of gas into a medium. The method and apparatus in accordance with the present invention are especially applicable in the bleaching plants of the wood processing industry for mixing gaseous bleaching chemicals into pulp and to bleaching process of pulp, in which the mixing method and apparatus in accordance with the present invention are applied. An excellent application is mixing ozone-containing gas into a fiber suspension flowing in a pipe line and an ozone bleaching process. The previously known methods and apparatuses have not been able to mix satisfactorily large volumes of gas, about 50 % of the total volume of the flow, into the medium flow. In the method in accordance with the present invention the mixing is carried out in a strong shear force field efficiently and uniformly, whereafter the fiber network of the medium is allowed to separate in the flow as bubbles, but remains in the plug flow in the fiber network.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	LJ	Liechtenstein	SK	Slovak Republic
CI	Côte d'Ivoire	LK	Sri Lanka	SN	Senegal
CM	Cameroon	LU	Luxembourg	SU	Soviet Union
CS	Czechoslovakia	MC	Monaco	TD	Chad
CZ	Czech Republic	MG	Madagascar	TG	Togo
DE	Germany	ML	Mali	UA	Ukraine
DK	Denmark	MN	Mongolia	US	United States of America
ES	Spain			VN	Viet Nam
FI	Finland				

METHOD AND APPARATUS FOR MIXING A FIRST MEDIUM TO A SECOND  
MEDIUM AND A BLEACHING PROCESS APPLYING SAID METHOD

The present invention relates to mixing a first medium into  
5 a second medium. The present invention especially relates  
to mixing gas to a medium, but it may as well be applied,  
for example, for mixing liquids, since mixing of gas has  
considerably higher requirements than the others both on  
the mixers and mixing methods. The method and apparatus in  
10 accordance with the present invention are especially  
suitable for mixing gaseous bleaching chemicals, such as  
oxygen or ozone, used in the bleach plants of the wood  
processing industry, and for the pulp bleaching process  
applying the mixing method and apparatus in accordance  
15 with the present invention. An excellent applicion is mixing  
ozone-containing gas with fiber suspension flowing in a  
pipe and an ozone bleaching process.

The main objective of the present invention is to develop  
20 a method of and an apparatus for mixing large volumes of  
gas into a medium. Further, since the chemical to be added  
may be extremely rapidly reacting, such as ozone, said  
preconditions set great demands on the method and apparatus  
to be developped.

25 In most of the modern bleaching plants very often large  
volumes of gas are desired to be mixed into a medium  
consistency fiber suspension, which means that the  
consistency of the fiber suspension is approximately 10-18  
30 % and it must be possible to mix a large volume of gas  
therewith. In other words during the mixing process  
approximately 40 to 80 % of the medium is fiber suspension  
and approximately 20 to 60 % gas, the proportion of the  
gas most usually being approximately 30 to 50 %. It is  
35 difficult to have a uniform feed of such a large gas volume  
and to reach a good mixing result, because gas is separated  
due to local pressure differences to areas of lower  
pressure, if possible. The non-uniform mixing results on

the increase of chemical loss, which further results in a non-uniform bleaching and in poorer runnability of the process.

- 5 The use of above mentioned ozone as a bleaching chemical in bleaching will become more and more popular in the future. There is an ongoing transition from pilot testing to applications in a mill scale, which leads to even higher demands on the apparatus due to the characteristic behavior
- 10 of ozone. Ozone may be produced and used with the modern technique only in very small proportions, whereby most (usually more than 90%) of the chemical to be mixed with the pulp to be bleached is in fact inert carrier gas compared with the ozone. The result is, of course, that the
- 15 volume of the gas to be mixed is large. Another significant point is that ozone reacts very rapidly with the material in the fiber suspension. Thus the mixing must be at the same time both very quick, efficient and also uniform in result. Since the ozone immediately reacts with all fibrous
- 20 material it encounters, the ozone-containing gas may not be allowed to meet only a particular portion of a suspension for a single moment, because it will result in a very uneven bleaching. According to the present technology ozone is not at all a selective chemical and it
- 25 reacts equally efficiently both with the fibrous material and the lignin to be removed or bleached. In other words, if the ozone dosing for a portion of the suspension is excessive, the ozone quickly causes damage also in the suspension, resulting, of course, in poorer quality of the
- 30 bleached pulp. Thus the mixing must be very uniform right from the beginning. Due to the non-selectivity the ozone cannot also not be overdosed and also not for the reason that ozone is an expensive chemical.
- 35 Ozone may be industrially produced only in relatively dilute mixtures. In other words only 5 to 10 % of the gas to be fed for the bleaching, is ozone the rest operating merely as a so called carrier gas. The carrier gas is in

most cases either oxygen or nitrogen. Therefore, approximately 10 to 20 times the volume of the ozone carrier gas must be fed and mixed although relatively small volumes of ozone are otherwise sufficient for the bleaching.

5

Some prior art mixers in the use of cellulose industry as well as their applicability in efficient and uniform mixing of large volumes of gas are studied more in detail below.

- 10 US Patent 4,416,548 illustrates an embodiment, in which the gas to be mixed is introduced into the frontside of a cylindrical rotor of an apparatus slightly resembling a centrifugal pump to a point where the pulp flowing axially along the suction duct is divided fan-like into a radial  
15 flow bringing the gas therewith to the rim of the cylindrical rotor. The flow turns there again axial, flowing, for example, between the pin-like members stationary mounted on the rotor housing and on the outer rim of the rotor to a spiral discharge chamber of the  
20 apparatus. The operation of the apparatus is based on that the pin-like members of the rotor pass the members of the housing very close generating a very strong shear force field mixing the chemical effectively to the pulp. The apparatus has two significant defects or disadvantages  
25 considering the purpose of the present invention. Firstly, the gas is fed into the center of the rotor into the relatively slowly flowing pulp, which, for example, when feeding ozone, results in a local overdose and damage of cellulose in the particular portion of the pulp. In order  
30 to be able to bleach the whole pulp amount, some kind of an overdose should be fed into the mixer, even with a risk of damaging the cellulose. Secondly, there is the disadvantage that subsequent to the efficient "pin mixing zone", pulp is allowed to be quickly discharged into a  
35 wider space, a spiral. Consequently, a zone of lower pressure is generated, in which the gas in the pulp is easily separated by the centrifugal force from the fiber suspension, which is still in a fluidized stage. Thus when

the consistency of the pulp increases and the pulp forms a plug flow in the discharge channel gas is entrained therewith in large bubbles. As a result therefrom the ozone which possibly still has not reacted in the gas would  
5 still react only with the fibers defining the gas bubbles.

FI patent 76132 illustrates a construction which to some extent resembles the arrangement in accordance with the US publication. The apparatus, however, is evidently a  
10 centrifugal pump, the impeller vanes of which are arranged two-piece in such a way that it is possible to fit a number of feed and mixing pins for the chemicals between said parts. Thus the feed of chemicals to a strong field of shear forces, is carried out in an orthodox manner but the  
15 pulp is discharged from the mixing zone to the spiral of the centrifugal pump, in which the pulp is, as known, subjected to intense centrifugal forces, due to which gas is separated from the pulp to form its own layer. The result is the same as above.

20 As a third example of the prior art is an arrangement disclosed in US Patent 4,305,894 comprising an axial flow pump, a rotor thereof and mixing means for gas. The liquid, with which the gas is intended to be mixed, is drawn by  
25 the rotor to a cylindrical suction duct, into which gas is fed immediately after the rotor in the flow direction through a pipe surrounding the axis of the rotor. A stationary blade is mounted on the outer surface of the pipe immediately after said gas feed to generate together  
30 with a liquid, strongly circulating in the duct, a field of shear forces in the liquid so that gas is mixed with the liquid. Additional efficiency to the mixing may be brought about by adding ribs or like on the wall. The apparatus does not, however, guarantee a uniform mixing,  
35 because the diameter of the suction duct is rather large and the gas is fed into the center of the flow. It is not possible to ensure that the gas in the apparatus would be able to flow into contact also with the liquid flowing on

the outermost layer of the flow, but it is assumed that the gas is mixed with the liquid flowing relatively close to the axis and the liquid in the outermost area of the suction duct remains without gas. When ozone is used, the non-uniform mixing results in non-uniform bleaching result and damage of cellulose because of a local overdose.

A fourth prior art publication worth mentioning is DE 2920337, which generally describes the utilization of the fluidization and different applications thereof, giving an example of mixing liquid or gas into fiber suspension. Said embodiment is illustrated primarily in Figs. 1 - 4, of which the construction of Fig. 2 comprises a cylindrical rotor positioned substantially axially in the flow channel, the outer surface of the rotor as well as the inner wall of the flow channel being provided with protrusions. The chemical, gas or liquid, to be mixed is introduced into the rotor through the shaft of the rotor, from the surface of which the chemical is fed to a relatively narrow fluidization zone between the rotor and the wall of the flow channel. It may be assumed of said construction that the mixing of gas into the suspension is uniform, but said apparatus still has some significant defects. Firstly, the illustrated rotor is rather short, which as such is an orthodox arrangement considering the energy consumption and also when the volume of the gas to be mixed is not very great or when the intention is to give no time to the chemical to react with the suspension. However, what is obtained with the mixer described above is a relatively high circumferential speed of the suspension causing the separation of the gas in the area immediately subsequent to the rotor when centrifugal force forces the suspension to the wall of the flow channel and the gas flows to the center of the flow. Said separation tendency in the arrangement according to the publication is so strong also because the axial cross-section of the rotor is rectangular, whereby the pulp being discharged from a rather narrow fluidization zone arrives to a large flow channel. There a

local zone with a strong low-pressure effect (i.e. a big pressure difference) is generated and thus gas can readily separate as large bubbles to the center of the flow.

5 A second embodiment illustrated in DE publication 2920337 (Figs. 3 and 4) comprises a similar rotor, which is mounted to the flow channel transversely in such a way that the suspension must pass through a narrow gap to the backside of the mixer rotor, where a throttling point of the flow  
10 channel is arranged. The mixing process corresponds to the previous embodiment, but is shorter of its duration. The problem is that the suspension is allowed to be discharged from the narrow fluidization zone into a quickly widening channel, whereby gas is able to separate as large bubbles  
15 from the suspension.

As is seen from the prior art review above only few previously known apparatuses are able to mix a gaseous chemical quickly and presumably also relatively uniformly  
20 into the fiber suspension. Yet, until now, it has always been mixing of relatively small volumes of gas and/or slowly reacting chemicals into the pulp. Thus it is in a way logical that no arrangements in accordance with the prior art can ensure the mixing of large volumes of gases  
25 into the pulp so that the gas would also remain uniformly mixed with the pulp subsequent to the mixing.

The objective of the present invention is to eliminate the disadvantages of the prior art apparatuses and to ensure  
30 that also large volumes of gases are uniformly mixed with the pulp and that they remain mixed with the pulp also when the pulp is discharged from the mixer to a flow channel or a reaction vessel.

35 It is possible to further design the mixing apparatus in accordance with the present invention to be applied for carrying out the actual ozone bleaching in such a way that the carrier gas and the possibly excessive ozone are removed



by means of the same apparatus and possibly returned by means of a second mixing apparatus to the next bleaching stage or step, whereby the term "displacement bleaching" may well be used. Said displacement bleaching refers to a

5 bleaching, in which a very rapidly reacting chemical is fed into pulp and mixed with the pulp to be treated in a relatively long axial distance (the distance is, of course, affected by the reaction speed of the chemical). The idea, however, is that, when the untreated pulp reaches the

10 mixer, it is mixed with a certain amount of chemicals (in this example ozone), which immediately reacts, leaving no or hardly any reactive chemical in the gas-pulp mixture, only so called carrier gas. When new chemical mixture is fed in the same mixer and mixed into the pulp it pushes

15 the "old" carrier gas from thereahead, which justifies the use of the term "displacement bleaching".

Characterizing features of the method in accordance with the present invention are

- 20 - to feed gas in the first phase into a fluidized medium flow in a narrow mixing channel;
- to dampen the shear force field of the gas-medium-suspension in the second phase and to allow a plug flow to be formed in the medium, whereby the gas remains uniformly
- 25 distributed in said plug flow.

It is again a characterizing feature of the apparatus in accordance with the present invention that the apparatus comprises a mixer body, an inlet channel for medium, a

30 substantially annular mixing channel, a discharge channel and a rotor rotatable in the mixing channel and that the rotor is tapering in the direction of the flow.

It is a characterizing feature of the bleaching process applying the method in accordance with the present invention

35

- to feed the bleaching chemical into an annular mixing channel;

- to mix the bleaching chemical into a medium which is in a fluidized state;

- to further agitate the medium allowing the chemical to react with the medium;

5     - to discharge the medium from the mixing channel to the discharge channel; and

- to remove residual chemical from the medium in the discharge channel and/or in the end portion of the mixing channel.

10

The method and apparatus in accordance with the present invention are described more in detail below, by way of example, with reference to the accompanying drawings, in which

15     Fig. 1 illustrates an axial sectional view of a preferred embodiment of an apparatus in accordance with the present invention;

Fig. 2 illustrates a sectional view of an apparatus of Fig. 1 via line A-A;

20     Fig. 3 illustrates a preferred embodiment of the apparatus in accordance with the present invention;

Figs. 4a and 4b illustrate a detail in accordance with a preferred embodiment of the present invention;

25     Figs. 5a and 5b illustrate a detail in accordance with a second embodiment of the present invention;

Fig. 6 illustrates a detail in accordance with a third embodiment of the present invention;

Fig. 7 illustrates a rotor in accordance with a preferred embodiment of the invention;

30     Figs. 8a - 8d illustrate arrangements in accordance with preferred embodiments of the present invention;

Figs. 9a and 9b illustrate two preferred applications of the method and apparatus in accordance with the present invention for a bleaching process; and

35     Fig. 10 illustrates yet another application of the method and apparatus in accordance with the present invention for a bleaching process.

Figs. 1 and 2 illustrate a preferred embodiment of an apparatus in accordance with the present invention, comprising bearing, drive and sealing unit 12 and a mixing portion 14. The above mentioned unit 12 may be considered to be of conventional construction, the details of which are neither shown nor described here. The mixing portion 14 comprises a rotor body 16, an inlet opening 18 and inlet channel 20 for pulp both mounted in said body 16, a mixing channel 22, a discharge channel 24 and a shaft 26 connected to the drive unit and a rotor 28 connected to the end thereof. The inlet channel 20 for pulp may be radial, but it may as well be tangential either in the rotational direction of the rotor 28 or preferably feeding pulp against said direction, as particularly pointed out in Fig. 2. The mixing channel 22 is substantially cylindrical, or more accurately annular, and it is surrounded in the embodiments shown in the drawings by two gas feed rings 30 mounted to the rotor body 16, said rings being preferably, for example, of sintered metal, ceramics or even very finely perforated metal plates so that the size of gas bubbles is as small as possible when gas is fed into the pulp. Of course, it is possible for the number of the feed rings 30 to vary from the above mentioned. As can be seen from the drawings, four gas inlet conduits 32 are arranged to the wall of the mixing channel, through which conduits the treating chemical is uniformly fed to an annular chamber 34 outside the feed rings. At least two inlet conduits 32 are preferably required to ensure that the feed of the gas from the ring to the mixing channel is sufficiently uniform, though some applications may function well enough with only one inlet conduit. Preferably, although not necessarily, the walls of the mixing channel are provided with axial ribs 36 in addition to said feed rings 30 to intensify the mixing effect.

35

The rotor 28 mounted on the shaft 26 is substantially cylindrical in the mixing channel portion and is provided with axial ribs 38 according to the drawing, the purpose

of which is to generate such an extensive shear force field together with the ribs 36 possibly mounted on the wall of the mixing channel 22 so that even large volumes of gas are mixed into the pulp uniformly. One substantial requirement for the efficient and economic operation of the rotor is that distance between the walls of the rotor 28 and the mixing channel 22 is not too large or that the distance between the ribs 38 of the rotor 28 and said wall or the ribs 36 arranged according to the drawing, on said wall is not very long.

Fig. 3 illustrates a preferred embodiment for ribs 38' and 36' of both rotor 28 and the wall of the mixing channel 22, which according to the drawing are incontinuous so that both ribs 36' and 38' are cogged, either so that they are formed by a row of protrusions attached on the wall surface of the rotor/mixing channel or that they are formed of continuous ribs 36' and 38', which have protrusions and lower portions, in other words recesses therebetween. In another embodiment the protrusions of the counter surfaces are interlaced in such a way that said protrusions may, if as strong shear force field as possible is required, fit in the recess of the counter rib. In some cases it is preferable to arrange said ribs inclined and ascending relative to the axis, whereby they accelerate the pulp both tangentially and axially. This kind of alignment of ribs may, of course, be applied also to the continuous ribs shown in Fig. 1.

A substantial and important feature relative to the operation of the rotor is the length of the mixing portion, the mixing zone, in other words the length of the area, in which the pulp is subjected to such an amount of shear forces that the mixing is effective and uniform. The length of said area is affected by, for example, following:

- volume of gas being mixed;
- whether the reaction chemical, for example ozone, is

desired to react practically speaking in the whole of said area;

- energy consumption.

- 5 Of said features at least the second and third are counter features, because the reaction of ozone requires some time which again requires a long, energy-consuming mixing zone. It is the objective of the arrangement in accordance with our invention that the length of the mixing portion of the  
10 rotor 28 is as small as possible without risking the efficiency and uniformity of the mixing.

A substantial portion in the mixer in accordance with the present invention is a slowly tapering tip portion 40 of  
15 the rotor, preferably it may be of its shape "a reverse Laval-nozzle" or at least very much resembling it for two reasons. Firstly, if the chemical to be mixed is slowly reacting, for example oxygen, whereby the chemical-pulp mixture is to be fed subsequent to the mixing into a  
20 reaction vessel, said mixture must be supplied from the mixer to the vessel so that the large volume of fed gas does not separate, as in the prior art apparatuses, from the fiber suspension immediately subsequent to the mixing zone. Said alternative is discussed partially when  
25 describing Fig. 1 and especially Figs. 4 - 6. Secondly, if the chemical to be mixed is rapidly reacting, as ozone is supposed to be at least according to some sources, the actual bleaching reaction takes place in the mixer itself, whereby the residual chemicals and/or the carrier gas may  
30 be separated from the mixture utilizing the mixer. Said alternative is discussed in connection with Figs. 7 and 8.

In the embodiment of Fig. 1 a discharge channel 24 is conically widening, whereby as from an annular mixing  
35 zone/mixing channel 22 the flow channel steadily widens. The shape of the preferably vertical discharge channel 24 resembles a Laval-nozzle, in other words the walls are slightly curved of their cross-section, whereby the flow

remains attached to the walls and does thus not cause separation of gas from the suspension. It is also possible to arrange the walls of the discharge channel 24 straight, in other words conical, whereby the total value determining the angle of the extension should preferably be below 8°. The purpose of the expansion of the flow channel when treating the mixture of slowly reacting chemicals and pulp is that the fluidized suspension having shear force fields forms fiber networks as quickly as possible, said fiber networks binding small gas bubbles therein before they have time to accumulate to larger bubbles or even to form a gas core in the center of the flow.

It is substantial for the dampening of the fluidization and the generation of the fiber networks to slow down the circumferential speed of the circulating flow generated by the rotor 28 in the mixing zone as quickly and efficiently as possible. For this purpose the surface of the tapering tip portion 40 of the rotor is in one of the embodiments polished very smooth, so as not to be able to generate any turbulence close to it or not to maintain the circulating movement of the pulp. In order to be able to slow down the speed of the flow quickly, the surface of the discharge channel 24 in Fig. 1 is provided with low ribs 42 (axially shown in the drawing) for stopping the circulating flow. As for the optimal operation of the apparatus, it is very important that said low ribs 42 are accurately directed so that they steadily turn the flow of the pulp circulating more or less in the direction of the rim gradually to an axial flow without generating turbulence to the surface layer of the suspension. Another requirement for the ribs is that, unless their direction is optimal, they may not generate turbulence in the surface layer, in other words pressure changes, which bring about separation of gas in the areas of lower pressure. In such a case decelerating ribs would have to be used that are very low at the first end. The height of the ribs is tended to keep so low that the ribs only prevent the circulation of the fiber layer

accumulated on the surface of the flow channel thus facilitating the formation of the fiber network. When the circulating movement is stopped the direction of the flow changes gradually to axial, the fibers stick to each other and the fiber network begins to form. Then the height of the decelerating ribs may be slightly increased in accordance with Fig. 1, whereby a larger and larger portion of the fiber flow joins the fiber network quickly forming a plug flow. Of course, in some cases also axial ribs 42 may be used, as in Fig. 1, whereby the height of the ribs has to be determined more accurately than with the spirally wound ribs. The purpose of said embodiment of the present invention, which relates to mixing of slowly reacting chemicals, is to form the plug flow so quickly that especially the gaseous chemicals do not have time to accumulate as large bubbles, but they remain uniformly divided in the fiber network.

It must be noted that the mixing channel does not have to be defined by two cylindrical surfaces. It may, for example, be defined by two conical surfaces or one conical surface and one cylindrical surface. Also the direction of the taper of the cones may be either to the same direction or to opposite directions. An embodiment worth mentioning is a construction in which the sectional area of the surface of the mixing channel widens to the flow direction, whereby it is logical to arrange the outer wall of the channel to expand conically and to leave the rotor cylindrical from the mixing channel portion. It is, however, possible to arrange both members conical, and even at the same opening angle, whereby the increase of the cross-sectional area is caused by the mere increase of the radius of the channel. Of course, for example, the conicalness of the rotor, as well as that of the mixing channel itself, may be arranged to extend only to a portion of the length of the mixing channel. Also other than cylindrical and conical surface forms are possible, but their use is restricted by practical requirements in the manufacture. By arranging the mixing

channel widening it is sometimes possible to leave the discharge channel cylindrical. This may also come into question, for example, in such cases when relatively small gas volumes are mixed into a dilute pulp at low rotational speed of the rotor, whereby the shear force field easily dampens merely by decreasing the cross-sectional area of the rotor in the discharge channel portion.

Figs. 4a and 4b illustrate another way, alternative to ribs 42 on the wall of the flow channel, to decelerate the circulating movement of the fiber suspension in the discharge channel 24. Blade-like members 52 are arranged to the joint flange of the discharge channel 24 and a pipe attached thereto to extend towards mixing channel. The purpose of said members 52 is, of course, to decelerate the circulating movement of the pulp in the discharge channel so as to form a fiber network as quickly as possible. The members 52 must, however, be formed very carefully, so as to prevent the fiber suspension being discharged as a spiral flow from the mixing channel 22 from forming a vortex around the members, whereby a gas bubble would easily be formed as a result of a phenomenon corresponding to the cavitation/cavitating. Fig. 4b especially illustrates, how the blade-like members 52 in a preferred embodiment are located in the discharge channel 24. The drawing also illustrates a preferred cross-sectional form of the blades, which preferably does not form any pressure field around it to facilitate the separation of gas from the pulp. The direction of said members may either be substantially parallel to the direction of the axial flow in the discharge channel, curved in such a way that they turn the flow axially or also possibly bent in such a way that they are positioned always perpendicular to the circulating flow.

Fig. 4a yet discloses ribs 36 and ribs 38 of the rotor on the walls of the mixing channel. According to a preferred embodiment the ribs 38 of the rotor do not extend as far in the flow direction as the ribs 36. In other words, the



effect of the rotor rotating the pulp may be terminated earlier, whereafter the circulating movement of the pulp in the mixing channel lasts some time to maintain the pulp in a fluidized state. At the same time the circulating movement slows down facilitating the deceleration of the circulating movement in the discharge channel. It has also been noted to be advantageous if the ends of the ribs are inclined, the height of the ribs decreasing to zero. The purpose thereof is to prevent the discharge of gas bubbles possibly accumulated behind the ribs, in other words to the so called lee side, full sized into the flow. By decreasing the height of the ribs the strongly turbulent pulp breaks the bubbles with the inclined edge of the rib, whereby the gas mixes better into the pulp.

15

Figs. 5a and 5b disclose a third alternative to increase friction surface in the area of the discharge channel 24. Members 54 and 56 formed of cylindrical or slightly conical surfaces are added in the embodiment of the drawing inside the discharge channel 24, the purpose of said members being only to increase the friction surface slowing down the circulating movement of the suspension, in other words generating a shear force field decelerating the circulating movement. Said surfaces may be arranged in the distance of 10 to 50 mm from each other, whereby their effect is most efficient as a decelerator of the circulating movement and a generator of a fiber network. In some cases it is possible to add in the middle of the members 54, 56 a stationary shaft to increase deceleration in the pulp circulating in the center of the discharge channel 24. The members 54, 56 are attached preferably from their wider edge to the joint flange 50 of the discharge channel 24. It is, of course, possible to support said members from their opposite ends to the wall of the discharge channel in order to eliminate a possible vibration, as is done by bars 58 in Fig. 6a. Figs. 5a and 5b disclose a way of arranging said members 54 and 56 inside the discharge channel 24. It is, however, possible to arrange all members to begin from the same

axial level either from the end of the rotor 28, prior or subsequent thereto. It is also possible to increase the distance of the members from each other in the discharge end also so that a number of the members do not extend as far as the others, for example, so that only every other member extends to the joint flange 50. It is also possible that said members 54 and 56 are not exactly rotationally symmetric, but are formed of slightly waved material, whereby their surface forms a considerably higher friction than the smooth cylinder or cone.

Fig. 6 discloses yet another efficient way of decelerating the circulating movement of the fiber suspension. The drawing relates to one of the embodiments, in which the flow direction is forced to change from parallel to the rim of the mixing channel to axial flow parallel to the pipe line subsequent to the mixer. Said change is brought about by arranging spiral strips or blades 70 at a slightly ascending angle of 4 - 10 grades from the first end of the discharge channel 24 or even prior to it to the wall of the discharge channel 24 (two strips placed opposite to each other shown). The rise of the spiral strips 70 is increased relatively quickly, whereby the movement parallel to the rim changes to axial. It is, of course, essential that the angle must be increased steadily and local lower pressure zones in the flow must be avoided. The number of the spiral strips also determines a successful deceleration of the flow. If the number of the spirals is very low, the rotational speed does not decelerate enough or the deceleration brings about local areas of lower pressure so that gas is allowed to separate from the flow. In the performed experiments it has been noted that the number of the spiral strips should vary between 3 to 10 according to the diameter of the discharge channel and also according to the rotational speed of the rotor and the volume of gas and consistency of the pulp.

Yet another way of decelerating the rotational movement of the suspension flowing from the mixing channel is to arrange one or more plates with openings perpendicular to the shaft or at least in an angled position relative to the axial direction in the discharge channel, whereby the kinetic speed of the suspension parallel to the rim quickly slows down when flowing through the openings.

It is a characterizing feature of another embodiment of the present invention primarily relating to the mixing of rapidly reacting chemicals, the reaction thereof in the mixer and the discharge of residual chemicals/gases and/or carrier gases from the mixer, illustrated in Fig. 7, that the tip portion 40 of the rotor is provided with gas discharge openings 44, through which excessive gas in the fiber suspension may be drawn or guided away. In some cases it is also possible to perforate a portion of the rotor surface 28 in the mixing channel area to intensify the discharge of gas. Said portion locates at the discharge end of the mixing channel. The illustrated embodiment may be applied, for example, in ozone bleaching, in which a mixture of ozone and carrier gas is mixed into the pulp, whereby at least the carrier gas or a portion thereof may be separated already in the tip area of the rotor. Also the excessive volume of ozone may be removed by utilizing the embodiment of the drawing, if the reaction time of ozone is considered to be sufficient in the mixing zone. Gas in the illustrated embodiment is led beforehand from the interior of the rotor 28 in a manner known per se, for example, through the gas-separating centrifugal pumps along the shaft of the rotor either to further treatment, cleaning or to be utilized, for example, in some other bleaching stage. It is also a characterizing feature of the above-mentioned embodiment of said construction alternative using ozone that the flow speed of the fiber suspension in the mixing zone is appropriate to the ozone, which is the chemical to be supplied, to react properly with the fiber suspension in the mixing zone. When

practically speaking all of the ozone has reacted, the gas that is left, being mainly carrier gas, may be removed through the tip portion of the rotor as efficiently as possible. In the arrangement in accordance with said embodiment, the smoothness of the surface of the rotor is not important. It is actually better for the gas separation that the surface of the rotor is at least to some extent uneven, rough or even provided with small blades, ribs or like.

10 Figs. 8a, 8b, 8c, and 8d disclose an apparatus in accordance with a preferred embodiment of the present invention more in detail. The drawings illustrate in a way the rotationally symmetric deceleration members already  
15 described in connection with Figs. 5a and 5b, which are here referred to as 74 and 76. In said embodiment a pipe 78 with a relatively small diameter is mounted in the middle of said members, extending right from the tip portion of the rotor 28 to the joint flange 50 and further to the  
20 outside of the apparatus. Moreover, the tip portion 40 of the rotor does not have to be polished anymore, but rough to some extent, as was described in connection with the description relating to the previous drawing. The purpose of the rotor is first of all to generate with the tip  
25 portion 40 some turbulence around the rotor so that gas tends to separate as a thin layer therearound. Therefrom the gas flows further towards the tip of the rotor to the area of the smallest diameter, wherefrom it is discharged along pipe 78. The pipe 78 is, when required, connected to  
30 a vacuum source or to some other appropriate apparatus (not shown). The objective of this embodiment is to enable a rapid bleaching so that a gaseous chemical is led by the rotor 28 to a fluidized pulp layer, allowed to flow through said layer and to react with the lignin of the fibers and  
35 the residual gas is separated by the tip portion 40 of the rotor. At this stage and depending on the reaction speed of the chemical also the displacement bleaching described above may come into question. The apparatus operates, for

example, in such a way that when gas accumulates forming a bubble around the tip portion of the rotor it rises as the lightest to the pipe and fills the pipe 78. By adjusting the volume of gas being discharged from the pipe the fibers  
5 may be prevented from flowing in to the pipe 78. A way (Fig. 8b) to complicate the flow of the fibers to the pipe 78 is to provide the tip portion of the rotor with an open portion or with an axial recess 41, which of course is filled with gas, because the relatively high axial flow  
10 speed of the fiber suspension carries the suspension past the recess and the fiber suspension is also affected by a considerably strong centrifugal force, which is due to the rotational speed.

15 Fig. 8c yet illustrates a way of discharging gas from the top of the rotor. The top of the rotor 28 is provided with an opening for leading the gas into the rotor and out therefrom via a known route. Fig. 8d illustrates yet a way of generating a local shear force field to the top of  
20 the rotor intensifying the gas separation, by mounting small blades, ribs or like to said tip area. By combining said embodiment, for example, with the deceleration members shown in Fig. 8a an embodiment is obtained, in which a fiber network is allowed to be formed of the suspension in  
25 the outer layers of the discharge channel, but gas is intentionally separated from the inner flow layer.

Besides the embodiments shown in the drawing, also other arrangements are possible in the separation of gas. It is  
30 possible to cut the rotor so that the tip thereof remains blunt, whereby gas is easily separated to the discharge side of the rotor. If required blades mounted as an extension to the rotor to intensify the circulating movement of the pulp may be used to intensify the gas separation.

35

Figs. 9a and 9b illustrate two preferred applications of an apparatus and a mixing method in accordance with the present application. In Fig. 9a two mixers 10' and 10'' in

accordance with the present invention are connected in series in such a way that the pulp to be treated is introduced via a flow channel 80 into the mixer 10", led therefrom via a flow channel 82 into the mixer 10' and discharged therefrom to a pipe line 84. According to an embodiment at least the mixer 10' is preferably either similar to Fig. 7 or Fig. 8 (shown here). In other words a rapid bleaching is carried out in the mixer 10' as previously described in Fig. 7 and the separated residual gas is removed along a flow channel 86 from the mixer 10' and also from the so called second bleaching step. The gas is brought along the flow channel 86, for example, to a venturi-pipe-type mixer 88, in which the residual gas is drawn into and mixed with fresh bleaching chemical arriving along a flow channel 90 to the second mixer 10" and further introduced into the mixer 10". If so desired or required, the second mixer 10" may be a gas-separating mixer, whereby the residual gas is further to be led to one of the further treatment or further utilization stage. It is characteristic of the described process that the volume of gas to be introduced into the mixer 10' second in the flow direction of the fiber suspension is greater than the volume of gas to be supplied to the mixer 10" first in the flow direction.

As can be seen, the process in question is a so called counter current bleaching, in which a mixture of "clean" bleaching chemical and a "used" chemical removed from the second bleaching step is supplied to the first bleaching step, in other words to the mixer 10", whereby, of course, the amount of active chemical in the first stage is smaller. "Clean and non-used", fresh chemical is again fed to the second step.

Fig. 9b discloses a reverse bleaching process, in which fresh chemical is fed to the first mixer 10" and the residual gas, which is separated subsequent to the mixer 10" or in the mixer is mixed with fresh chemical and fed into the pulp in the mixer 10' of the second step.

Of course, it is possible that more bleaching steps of said type are arranged subsequently, whereby the return of the residual gas may also be arranged either only to the first step or always to the step preceding the removal or possibly also to the last step or the step following the removal. The way how this is done, depends on the amount of chemical fed to each step, the chemical contents, the chemical being fed as "fresh", etc.

Fig. 10 yet illustrates a process within the scope of the present invention. Number 90 refers to a conventional mass tower, which as such may be a bleaching or storage tower, from which the medium or high consistency pulp is preferably supplied by a fluidizing centrifugal pump 92 to a second fluidizing centrifugal pump 94 provided with a gas discharge and to the suction side of which in the effective range of the fluidizer the bleaching chemical is fed from the pipe 96. Residual gas, consisting either completely of a bleaching chemical or, for example, when ozone is used, of both the bleaching chemical and a so called carrier gas, is separated in the pump 94. The separated gas is led via a pipe 98 into an inlet pipe 100, for example, as described in the previous embodiment. The chemical mixture from the pipe 100 is fed to a mixer 102, which may be a mixer in accordance with the present invention separating gas. The gas to be separated is led from the mixer 102 in a previously known manner to another mixer 104, from which the pulp to be treated is discharged to a vessel 106, in which the bleaching chemicals are allowed to completely react. It is worth noting that the above described embodiment is completely exemplary. The basic idea is that now for the first time in the history a centrifugal pump is suggested to be used not only to mix a chemical to a pulp, but also to act as a "bleaching vessel" so that the ability of the centrifugal pump to separate large volumes of gas from pulp is utilized to separate the residual gas from the pulp. At the same point, as an

alternative, bleaching can be carried out in three subsequent mixers, as three step bleaching. Further, alternatively, pulp is fed to the fluidizing centrifugal pump 94 operating as a gas separator by another fluidizing centrifugal pump 92, whereby the pressure in the feed of the pump 94 facilitates the separation of the gas from the pulp.

Moreover, a method worth mentioning is to bleach pulp more efficiently than before by ozone. As mentioned earlier, ozone may be used due to practical reasons only in relatively low consistencies (5-10%). It has been, however, noted that due to an efficient, rapid and uniform mixing it is possible to use also higher ozone contents in the mixer in accordance with the present invention. Such is achieved by adding a semi-permeable membrane into communication with said porous surface, by means of which the ozone may partially be separated from the carrier gas. Thus greater ozone contents are obtained to the mixing zone, which leads to a considerably more efficient bleaching result.

Except for said ceramic, sintered or finely perforated gas feed rings it is possible to use in the gas feed quite a different technique. The gas inlet rings are provided with relatively large holes having a diameter of 1-3 mm, of which gas is injected in thin sharp jets to the pulp circulating in the mixing zone. By using said technique it is possible to achieve a more efficient penetration of gas into the pulp and the flow-through of gas from the pulp layer is accelerated.

As for the ozone bleaching, yet a method worth mentioning is to improve the total economy of the system. It is known that the ozone is generally manufactured in atmospheric conditions or slightly pressurized from oxygen, which is brought to the mill in a pressurized form. Immediately prior to the bleaching, in other words the feed to the



mixer, the pressure of the ozone (and the carrier gas) is raised to 7-15 bar by an expensive compressor. It has been noted, however, that it is completely possible to manufacture ozone in pressurized conditions from pressurized oxygen so that the obtained ozone remains pressurized throughout from the manufacture to the mixing, whereby said compressor is not necessary.

As seen above a new kind of a method and apparatus for mixing gas into a medium and a bleaching process applying the method are developed. Although several different apparatus variations are disclosed above, they are only meant to exemplify and clarify without any intention to restrict from what is given in the patent claims, which alone determine the scope of invention. Thus also many other alternatives are within the scope of invention. The above description also concentrates on the bleaching process and especially a bleaching process that uses ozone. However, the method and apparatus may as well be applied for mixing of gaseous chemicals or additives and also of liquid chemicals or additives. As for the detailed bleaching process described above also other bleaching processes may come into question. It is, for example, logical that the residual gas from one mixer may be led entirely to another bleaching step and not necessarily to the preceding or subsequent bleaching step as in the above described example. It is also possible that the oxygen to be separated as residual gas from the ozone bleaching is led to an oxygen bleaching stage or step and not mixed with a high ozone-containing gas.

CLAIMS

1. A method of mixing gas into a medium, whereby gas is fed to a medium flow being contemporarily intensively mixed, characterized in that
- 5       - in the first phase gas is fed into a fluidized medium flow in a narrow mixing channel; and
- in the second phase the shear force field of the gas-medium-suspension is dampened and a plug flow is allowed to be formed in the medium, whereby the gas remains uniformly distributed in said plug flow.
- 10
2. Method in accordance with claim 1, characterized in that gas is prevented from separating from the pulp by minimizing the factors maintaining the shear force field.
- 15
3. Method in accordance with claim 1, characterized in that the circulating flow is turned in the second phase to an axial flow.
- 20
4. Method in accordance with claim 1, characterized in that the circulating flow is subjected in the second phase to a decelerating shear force field, whereby the circulating movement decelerates and the flow is turned axial.
- 25
5. Method in accordance with claim 4, characterized in that the circulating flow is subjected to several decelerating shear force fields, which are in sequence and/or one within the other, whereby the rotational movement decelerates and the flow turns axial.
- 30
6. Method in accordance with claim 1, characterized in that the volume of gas fed to a mixing phase, corresponds to 20 - 60 %, preferably 30 - 50 % of the volume of the medium flowing to said phase.
- 35
7. Method in accordance with claim 1, characterized in that gas is fed in the form of small bubbles.

8. Method in accordance with claim 1, characterized in that gas is fed in thin sharp jets into the fluidized pulp layer, whereby the effect of chemicals immediately extends  
5 throughout the entire layer.

9. Method in accordance with claim 1, characterized in that

- as a third phase separating or intensifying the  
10 separation of gas from the medium to the outer part of the flow in the mixing phase or subsequent thereto by subjecting shear forces to the medium flow in the portion of the discharge channel and by allowing the gas to accumulate to the center portion of the discharge channel.

15

10. An apparatus for mixing gas into a medium, comprising a mixer body, feed means for gas therein, an inlet channel for medium, a substantially annular mixing channel, a discharge channel and a rotor rotatable in a mixing  
20 channel, characterized in that a rotor (28) tapers in the flow direction of the medium.

11. Apparatus in accordance with claim 10, characterized in that the cross-sectional area of the discharge channel  
25 (24) is at least partially widening in the flow direction of the medium.

12. Apparatus in accordance with claim 11, characterized in that the discharge channel (24) is provided with means for  
30 dampening the rotational flow of the medium and/or turning it substantially axial.

13. Apparatus in accordance with claim 12, characterized in that the wall of the discharge channel (24) is provided  
35 with members (42), the height of which increases measured from the wall in the flow direction of the medium.

14. Apparatus in accordance with claim 12, characterized in that members (52; 54, 56; 74, 76) are arranged in the discharge channel (24) within a distance from the wall of the channel (24) in order to subject the medium to a force field decelerating the rotational movement.
15. Apparatus in accordance with claim 14, characterized in that said members (52) are blades or like, extending towards the flow direction of the discharge channel and the cross-sectional shape of which resists the flow as little as possible.
16. Apparatus in accordance with claim 14, characterized in that said members (54, 56; 74, 76) are annular, substantially rotationally symmetric elements, the number of which is at least one and which are mounted substantially concentrically in the discharge channel (24).
17. Apparatus in accordance with claim 16, characterized in that said members (54, 56; 74, 76) are more in number so that the radial distance therebetween is 15 - 50 mm.
18. Apparatus in accordance with claim 14, characterized in that said member is a plate with openings, mounted perpendicular to the discharge channel (24) and through which the medium must flow when exiting the apparatus.
19. Apparatus in accordance with claim 10, characterized in that the wall of mixing channel (22) is provided with ribs (36) and the surface of the rotor (28) at the mixing channel is provided with ribs (38) so that the ribs (36) extend on the wall further towards the discharge channel (24) than the ribs (38) on the surface of the rotor (28) and that the end of at least one of the ribs (36, 38) on the discharge side is inclined.
20. Apparatus in accordance with claim 10, characterized in

that the cross-sectional area of the mixing channel (22) is widening in the flow direction.

21. Apparatus in accordance with claim 10 or 20,  
5 characterized in that the diameter of the rotor (28) grows in the flow direction at least on a portion of the mixing channel (22).

22. Apparatus in accordance with claim 10, characterized in  
10 that the center of the discharge channel in front of the tip (40) of the rotor (28) is provided with a gas discharge pipe (78).

23. Apparatus in accordance with claim 10, characterized  
15 in that the tip (40) of the rotor (28) is perforated or the point of the tip (40) is provided with an opening in order to separate the gas into the rotor, from where the gas is discharged further in a manner known per se.

20 24. Apparatus in accordance with claim 23, characterized in that the surface of the tip (40) of the rotor (28) is roughened or provided with small blades, ribs, or like members facilitating the separation of gas.

25 25. A bleaching process applying the method in accordance with claim 1, characterized by

- feeding a bleaching chemical is fed to an annular mixing channel;
- mixing a bleaching chemical is mixed with a medium  
30 being in a fluidized state;
- further agitating said medium contemporarily allowing the chemical to react with the medium;
- discharging said medium from the mixing channel to the discharge channel; and
- 35 - discharging residual chemical from the medium in the discharge channel and/or in the end portion of the mixing channel.

26. Bleaching process in accordance with claim 25, characterized by feeding the bleaching chemical through one limiting surface of the annular mixing channel into the medium and discharged close to the other limiting surface from the medium.
27. Bleaching process in accordance with claim 25, characterized in that the residual chemical is fed into a second bleaching phase or step.
28. Bleaching process in accordance with claim 27, characterized in that the residual chemical is fed together with fresh chemical to the second bleaching phase or step.
29. Bleaching process in accordance with claim 27 or 28, characterized in that the residual chemical is fed in the flow direction of the medium into one of the preceding or subsequent bleaching phase or step.
30. Bleaching process in accordance with claim 25, characterized in that the bleaching chemical is ozone, which is introduced with a carrier gas, which most usually is oxygen or nitrogen.
31. Bleaching process in accordance with claim 25, characterized in that the bleaching chemical is ozone, which is fed concentrated through a semipermeable membrane/membranes into a mixing channel.
32. Bleaching process in accordance with claim 25, characterized by
- feeding said bleaching chemical into a suction channel of a fluidizing centrifugal pump;
  - separating said residual gas from the medium in said centrifugal pump;
  - mixing said residual gas with fresh bleaching chemical; and

- feeding thus obtained chemical mixture to a second bleaching phase or step.

33. Bleaching process in accordance with claim 32,  
5 characterized by

- separating said residual gas from a second bleaching phase or step;

- mixing said residual gas with fresh bleaching chemical;  
and

10 - feeding thus obtained chemical mixture to a third bleaching phase or step.

34. Bleaching process in accordance with claim 32,  
characterized in that the medium to be treated is fed into  
15 said fluidizing centrifugal pump by a second pump, whereby  
the high pressure of the medium in the fluidizing  
centrifugal pump facilitates the gas separation from the  
medium.

## AMENDED CLAIMS

[received by the International Bureau on 10 March 1993 (10.03.93);  
original claims 1, 10 and 25 amended; other claims unchanged (6 pages)]

1. A method of mixing gas into a medium, whereby gas is  
fed to a medium flow being contemporarily intensively  
5 mixed, characterized in
  - feeding, in the first phase, gas into a fluidized  
medium flow in a narrow mixing channel; and
  - dampening, in the second phase, the shear force field  
of the gas-medium-suspension and allowing a plug flow to  
10 be formed in the medium, whereby the gas remains uniformly  
distributed in said plug flow.
2. Method in accordance with claim 1, characterized in  
preventing the gas from separating from the pulp by  
15 minimizing the factors maintaining the shear force field.
3. Method in accordance with claim 1, characterized in  
turning the circulating flow in the second phase to an  
axial flow.  
20
4. Method in accordance with claim 1, characterized in  
subjecting the circulating flow in the second phase to a  
decelerating shear force field, whereby the circulating  
movement decelerates and the flow is turned axial.  
25
5. Method in accordance with claim 4, characterized in  
subjecting the circulating flow to several decelerating  
shear force fields, which are in sequence and/or one  
within the other, whereby the rotational movement  
30 decelerates and the flow turns axial.
6. Method in accordance with claim 1, characterized in  
that the volume of gas fed to a mixing phase, corresponds  
to 20 - 60 %, preferably 30 - 50 % of the volume of the  
35 medium flowing to said phase.
7. Method in accordance with claim 1, characterized in  
feeding the gas in the form of small bubbles.



8. Method in accordance with claim 1, characterized in feeding the gas in thin sharp jets into the fluidized pulp layer, whereby the effect of chemicals immediately  
5 extends throughout the entire layer.

9. Method in accordance with claim 1, characterized in that

- separating the gas or intensifying the separation of  
10 gas, as a third phase, from the medium to the outer part of the flow in the mixing phase or subsequent thereto by subjecting shear forces to the medium flow in the portion of the discharge channel and by allowing the gas to accumulate to the center portion of the discharge channel.

15

10. An apparatus for mixing gas into a medium, comprising a mixer body, feed means for gas therein, an inlet channel for medium, a substantially annular mixing channel, a discharge channel and a rotor rotatable in a mixing  
20 channel, characterized in that a rotor (28) tapers in the flow direction of the medium.

11. Apparatus in accordance with claim 10, characterized in that the cross-sectional area of the discharge channel  
25 (24) is at least partially widening in the flow direction of the medium.

12. Apparatus in accordance with claim 11, characterized in that the discharge channel (24) is provided with means  
30 for dampening the rotational flow of the medium and/or turning it substantially axial.

13. Apparatus in accordance with claim 12, characterized in that the wall of the discharge channel (24) is provided  
35 with members (42), the height of which increases measured from the wall in the flow direction of the medium.

14. Apparatus in accordance with claim 12, characterized in that members (52; 54, 56; 74, 76) are arranged in the discharge channel (24) within a distance from the wall of the channel (24) in order to subject the medium to a force field decelerating the rotational movement.
15. Apparatus in accordance with claim 14, characterized in that said members (52) are blades or like, extending towards the flow direction of the discharge channel and the cross-sectional shape of which resists the flow as little as possible.
16. Apparatus in accordance with claim 14, characterized in that said members (54, 56; 74, 76) are annular, substantially rotationally symmetric elements, the number of which is at least one and which are mounted substantially concentrically in the discharge channel (24).
17. Apparatus in accordance with claim 16, characterized in that said members (54, 56; 74, 76) are more in number so that the radial distance therebetween is 15 - 50 mm.
18. Apparatus in accordance with claim 14, characterized in that said member is a plate with openings, mounted perpendicular to the discharge channel (24) and through which the medium must flow when exiting the apparatus.
19. Apparatus in accordance with claim 10, characterized in that the wall of mixing channel (22) is provided with ribs (36) and the surface of the rotor (28) at the mixing channel is provided with ribs (38) so that the ribs (36) extend on the wall further towards the discharge channel (24) than the ribs (38) on the surface of the rotor (28) and that the end of at least one of the ribs (36, 38) on the discharge side is inclined.

20. Apparatus in accordance with claim 10, characterized in that the cross-sectional area of the mixing channel (22) is widening in the flow direction.
- 5 21. Apparatus in accordance with claim 10 or 20, characterized in that the diameter of the rotor (28) grows in the flow direction at least on a portion of the mixing channel (22).
- 10 22. Apparatus in accordance with claim 10, characterized in that the center of the discharge channel in front of the tip (40) of the rotor (28) is provided with a gas discharge pipe (78).
- 15 23. Apparatus in accordance with claim 10, characterized in that the tip (40) of the rotor (28) is perforated or the point of the tip (40) is provided with an opening in order to separate the gas into the rotor, from where the gas is discharged further in a manner known per se.
- 20 24. Apparatus in accordance with claim 23, characterized in that the surface of the tip (40) of the rotor (28) is roughened or provided with small blades, ribs, or like members facilitating the separation of gas.
- 25 25. A bleaching process applying the method in accordance with claim 1, characterized by
- feeding a bleaching chemical to an annular mixing channel;
  - 30 - mixing a bleaching chemical with a medium being in a fluidized state;
  - further agitating said medium contemporarily allowing the chemical to react with the medium;
  - discharging said medium from the mixing channel to the
  - 35 discharge channel; and
  - discharging residual chemical from the medium in the discharge channel and/or in the end portion of the mixing channel.

26. Bleaching process in accordance with claim 25,  
characterized by feeding the bleaching chemical through  
one limiting surface of the annular mixing channel into  
5 the medium and discharging the residual chemical from the  
proximity of the other limiting surface from the medium.

27. Bleaching process in accordance with claim 25,  
characterized by feeding the residual chemical into a  
10 second bleaching phase or step.

28. Bleaching process in accordance with claim 27,  
characterized by feeding the residual chemical together  
with fresh chemical to the second bleaching phase or step.  
15

29. Bleaching process in accordance with claim 27 or 28,  
characterized by feeding the residual chemical in the flow  
direction of the medium into one of the preceding or  
subsequent bleaching phase or step.  
20

30. Bleaching process in accordance with claim 25,  
characterized in that the bleaching chemical is ozone,  
which is introduced with a carrier gas, which most usually  
is oxygen or nitrogen.  
25

31. Bleaching process in accordance with claim 25,  
characterized in that the bleaching chemical is ozone,  
which is fed concentrated through a semipermeable  
membrane/membranes into a mixing channel.  
30

32. Bleaching process in accordance with claim 25,  
characterized by

- feeding said bleaching chemical into a suction channel  
of a fluidizing centrifugal pump;
- 35 - separating said residual gas from the medium in said  
centrifugal pump;
- mixing said residual gas with fresh bleaching  
chemical; and

- feeding thus obtained chemical mixture to a second bleaching phase or step.

33. Bleaching process in accordance with claim 32,  
5 characterized by

- separating said residual gas from a second bleaching phase or step;

- mixing said residual gas with fresh bleaching chemical; and

10 - feeding thus obtained chemical mixture to a third bleaching phase or step.

34. Bleaching process in accordance with claim 32,  
characterized by feeding the medium to be treated into  
15 said fluidizing centrifugal pump by a second pump, whereby the high pressure of the medium in the fluidizing centrifugal pump facilitates the gas separation from the medium.

## STATEMENT UNDER ARTICLE 19

The Examiner has cited to a SE document 462857, which discloses an oxygen mixer for mixing gaseous bleaching chemical into a fiber suspension. The apparatus disclosed in the document does not solve the problems, for which our device is developed.

Claim 1 of ours divides our method in two steps or phases; the first one being to introduce the chemical into a fluidized medium in a narrow mixing channel and the second one being to dampen the shear force field and thus facilitate the formation of plug flow.


First of all the medium in question in our application is usually a medium consistency fiber suspension i.e. the consistency being of the order of 5 to 20 %. The cited reference does not speak a word of the type of the medium.



Secondly, the mixing channel extends in a radial direction in the apparatus of the cited reference. Our channel is axially extending.

Thirdly, the SE document is silent to dampening of the flow. It could not even talk about allowing the fiber network to be formed since there is no indication of the existence of such prior to the mixing phase.

As to claim 10 we cannot understand how the SE document could be categorized as "X" since the apparatus disclosed in the SE publication has no tapering parts at all.

As to claim 25 the SE publication does not deal with separating residual chemicals from the medium.










FIG. 7




FIG. 4a






FIG. 5a






FIG. 6




FIG. 8a




FIG. 8d




FIG. 8c




FIG. 8b




FIG. 9a




FIG. 9b




FIG. 10

# INTERNATIONAL SEARCH REPORT

International Application No PCT/FI 92/00276

<b>I. CLASSIFICATION F SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>6</sup> According to International Patent Classification (IPC) or to both National Classification and IPC <b>IPC5: B 01 F 7/00, D 21 C 9/10</b>								
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; border: 1px solid black; padding: 2px;">Minimum Documentation Searched<sup>7</sup></div> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%; border: 1px solid black; padding: 2px;">Classification System</td> <td style="border: 1px solid black; padding: 2px;">Classification Symbols</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; vertical-align: top;">IPC5</td> <td style="border: 1px solid black; padding: 5px; vertical-align: top;">B 01 F; D 21 B; D 21 C</td> </tr> </table> <div style="text-align: center; border: 1px solid black; padding: 2px;">Documentation Searched other than Minimum Documentation to the extent that such Documents are included in Fields Searched<sup>8</sup></div> <p>SE,DK,FI,NO classes as above</p>			Classification System	Classification Symbols	IPC5	B 01 F; D 21 B; D 21 C		
Classification System	Classification Symbols							
IPC5	B 01 F; D 21 B; D 21 C							
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%; padding: 2px;">Category *</th> <th style="width: 60%; padding: 2px;">Citation of Document,<sup>11</sup> with indication, where appropriate, of the relevant passages<sup>12</sup></th> <th style="width: 30%; padding: 2px;">Relevant to Claim No.<sup>13</sup></th> </tr> </thead> <tbody> <tr> <td style="vertical-align: top; padding: 5px;">X</td> <td style="vertical-align: top; padding: 5px;">           SE, B, 462857 (INGERSOLL-RAND COMPANY)            10 September 1990, see figures 1-3;            claim 1  <div style="text-align: center; margin-top: 20px;">             ---              -----           </div> </td> <td style="vertical-align: top; padding: 5px;">           1,10,            25         </td> </tr> </tbody> </table>			Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>	X	SE, B, 462857 (INGERSOLL-RAND COMPANY) 10 September 1990, see figures 1-3; claim 1 <div style="text-align: center; margin-top: 20px;">             ---              -----           </div>	1,10, 25
Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>						
X	SE, B, 462857 (INGERSOLL-RAND COMPANY) 10 September 1990, see figures 1-3; claim 1 <div style="text-align: center; margin-top: 20px;">             ---              -----           </div>	1,10, 25						
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><sup>a</sup> Special categories of cited documents: <sup>10</sup></p> <p><sup>"A"</sup> document defining the general state of the art which is not considered to be of particular relevance</p> <p><sup>"E"</sup> earlier document but published on or after the international filing date</p> <p><sup>"L"</sup> document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p><sup>"O"</sup> document referring to an oral disclosure, use, exhibition or other means</p> <p><sup>"P"</sup> document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p><sup>"T"</sup> later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p><sup>"X"</sup> document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p><sup>"Y"</sup> document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p><sup>"&amp;"</sup> document member of the same patent family</p> </div> </div>								
<b>IV. CERTIFICATION</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border: 1px solid black; padding: 5px;">           Date of the Actual Completion of the International Search  <b>1st February 1993</b> </td> <td style="width: 50%; border: 1px solid black; padding: 5px;">           Date of Mailing of this International Search Report  <b>03 -02- 1993</b> </td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">           International Searching Authority  <b>SWEDISH PATENT OFFICE</b> </td> <td style="border: 1px solid black; padding: 5px;">           Signature of Authorized Officer  <b>Wiva Asplund</b> </td> </tr> </table>			Date of the Actual Completion of the International Search <b>1st February 1993</b>	Date of Mailing of this International Search Report <b>03 -02- 1993</b>	International Searching Authority <b>SWEDISH PATENT OFFICE</b>	Signature of Authorized Officer <b>Wiva Asplund</b>		
Date of the Actual Completion of the International Search <b>1st February 1993</b>	Date of Mailing of this International Search Report <b>03 -02- 1993</b>							
International Searching Authority <b>SWEDISH PATENT OFFICE</b>	Signature of Authorized Officer <b>Wiva Asplund</b>							



# **ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/FI 92/00276**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 08/01/93. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
SE-B- 462857	90-09-10	CA-A- 1218550	87-03-03
		DE-A-C- 3327508	84-02-09
		FR-A- 2531348	84-02-10
		GB-A-B- 2128492	84-05-02
		JP-C- 1409489	87-11-24
		JP-A- 59030981	84-02-18
		JP-B- 62014677	87-04-03
		SE-A- 8303458	84-02-07
		US-A- 4435085	84-03-06